




## Crystal LED Display System

### Main Features


#### Outstanding High Contrast

99% black occupancy thanks to Sony's unique ultra fine LED (0.003 mm<sup>2</sup>) technology.



#### Wide Viewing Angle


Nearly 180° without color shift and change in brightness.  
Not only horizontally but also vertically.




#### Fine Seamless Alignment

No seam, no bezel thanks to highly accurate alignment and uniformity adjustment.  
Free Style Combination, Free Size Installation, Free Aspect Ratio.

#### Installation Example



144 units (8K x 2K)



# Specifications



## Display Unit

Model	ZRD-2	ZRD-1
Surface	Low-Reflection	Clear Finish
Brightness	Max 1,000 cd/m <sup>2</sup>	
Contrast ratio	More than 1,000,000 : 1	
Viewing angle	Almost 180°	
Display native color space	140% of sRGB	
Application	Indoor	
Power consumption	Max 200W (per unit) Average 100W (per unit)	
Dimensions (W x H x D)	403.2 x 453.6 x 100 mm 15 7/8 x 17 7/8 x 4 inches	
Mass	10.0kg 22lb 0.74oz	

## Display Controller

Model	ZRCT-200	ZRCT-100
Maximum control number of display unit	72 (6unit/1port x 12port)	
Maximum input resolution	W3840 x H2160	
Video input	HDMI 2.0 x 2 HDCP Compliant, DisplayPort (DP1.2) x 2	DVI-D (Single Link) x 4*, DisplayPort (DP1.2) x 2
Maximum linkage number of controller	20	
Power consumption	90W	
Dimensions (W x H x D)	440 x 65 x 349 mm (without protrusions) 17 3/8 x 2 5/8 x 13 3/4 inches (without protrusions)	
Mass	6.3 kg 13 lb 14.2 oz	

\* HDCP Compliant

## Input Signal

### HDMI (ZRCT-200)

Resolution	Input frame rate*1	Input bit depth	Input color sampling
3840 x 2160	60P/50P	8bit	RGB 4:4:4*2 / YCbCr 4:4:4*2 / YCbCr 4:2:0
	60P/50P	12bit	YCbCr 4:2:2*2
	30P/25P/24P	12/10bit	RGB 4:4:4*2 / YCbCr 4:4:4*2
	30P/25P/24P	8bit	RGB 4:4:4 / YCbCr 4:4:4
	30P/25P/24P	12bit	YCbCr 4:2:2
1920 x 1080	60P/50P/30P/25P/24P	12/10/8bit	RGB 4:4:4 / YCbCr 4:4:4 / YCbCr 4:2:2*3
1280 x 720	60P/50P		
1024 x 768	60P		
800 x 600	60P		
720 x 480	60P		
720 x 576	50P		
640 x 480	60P		

\*1: 1,000/1,001 frame rate is also supported for 60p/30p/24p.

\*2: Strongly recommend using premium high speed HDMI cables.

\*3: 12bit only

### DisplayPort : Single Input (ZRCT-200 / ZRCT-100)

Resolution	Input frame rate*1	Color bit depth	Input color sampling
3840 x 2160*2	60P/50P/30P/25P/24P	8/10bit	RGB 4:4:4
1920 x 2160	120P*2 / 100P*2 / 60P/30P/25P/24P		
1920 x 1080	120P/100P/60P/50P/30P		

### DisplayPort : Dual Input (ZRCT-200 / ZRCT-100)

Resolution	Input frame rate*1	Color bit depth	Input color sampling
3840 x 2160*3	120P/100P	8/10bit	RGB 4:4:4

### DVI : 1 Input (ZRCT-100)

Resolution	Input frame rate*1	Color bit depth	Input color sampling
1920 x 1080	60P/50P/30P/25P/24P	8bit	RGB 4:4:4

### DVI : 4 Input (ZRCT-100)

Resolution	Input frame rate*1	Color bit depth	Input color sampling
3840 x 2160*4	60P/50P/30P/25P/24P	8bit	RGB 4:4:4

\*1: 1,000/1,001 frame rate is also supported. \*2: Only multi-stream is supported.

\*3: Supported by two input signals of 1920 x 2160, 120P. \*4: Supported by four input signals of 1920 x 1080.

## Applications



©2018 Sony Imaging Products & Solutions Inc. Reproduction in whole or in part without written permission is prohibited. Features and specifications are subject to change without notice. Screen images are simulated. The values for mass and dimension are approximate. "SONY" is a registered trademark of Sony Corporation. All other trademarks are property of their respective owners. Please visit Sony's professional website or contact your Sony representative for specific models available in your region.