

Nuvo®

8" Powered Subwoofer



The small-but-mighty 8" Powered Subwoofer packs hard-hitting bass into a discreet, compact enclosure. With a front-mounted woofer, port and efficient all-digital 100 watt amplifier, the NV-SUB8 adds a detailed low-frequency impact to smaller home theater or audio installations. Its cabinet is constructed of durable MDF for distortion-free bass response.

- **Powerful front-mounted 8" subwoofer ideal for small-medium sized audio installations**
- **Installation-friendly front-firing woofer and single port**
- **Compact design requires just over a square foot of space**
- **Durable MDF enclosure construction ensures distortion-free bass response**
- **Unfiltered LFE (low frequency effects) input, RCA stereo input and output, and USB port**
- **Signal-sensing power ON/OFF**
- **Variable crossover and phase adjustment**
- **Woofer has lifetime warranty and amplifier has two year warranty**
- **Efficient all-digital 100 watt amplifier**

The NV-SUB8 features signal-sensing power activation (optional setting) to automatically turn on the subwoofer when it receives a signal from the receiver. It will return to standby after 15 minutes of no signal.

Offering maximum versatility, the Powered Subwoofers were designed to integrate with almost any audio system. Unfiltered LFE / RCA stereo input and output let you easily connect to most modern receivers. And a convenient USB jack can power an optional wireless receiver. The variable crossover and phase controls allow you to match the Subwoofer output with the main speakers for premium performance and sound.



Nuvo® NV-SUB8 Subwoofer

Materials

Vinyl covered MDF cabinet

Output

Speaker Impedance	8 Ohms
Power Consumption	15 watts typical 120 watts max
Output Power	100 watts
Frequency	30Hz - 200Hz
Line Output Connector	RCA analog (pair)
Operating Temperature	5° - 35° C 41° - 95° F

Input

Line Input Connector	LFE / RCA analog (pair)
Input Voltage	110v - 220v (manual switch)
Line Input Overload	8 volts

Regulatory Approvals

cTUVus, CE-LVD
 US:FCC CFR Title 47 Part 15, Subpart B; CANADA:ICES-003
 EUROPE:CISPR32; EUROPE: EN 55032:2012;
 AUSTRALIA/NEW ZEALAND: RCM Standard AS/NZS CISPR32
 RoHS (Restriction of Hazardous Substances Directive 2002/95/EC)

Weight

Unit Weight (kg)	9.6 kg
Unit Weight (lbs)	21.2 lbs
Shipping Weight (kg)	11.5 kg
Shipping Weight (lbs)	25.3 lbs

Unit Size

Unit Size (mm)	330.2 L x 315 W x 348 H
Unit Size (inch)	13 L x 12.4 W x 13.7 H

Unit Size without feet

Unit Size (mm)	315 L x 315 W x 348 H
Unit Size (inch)	12.4 L x 12.4 W x 13.7 H

Shipping Specifications

Unit Size (mm)	449.6 L x 449.6 W x 449.6 H
Unit Size (inch)	17.7 L x 17.7 W x 17.7 H

Legrand reserves the right to change specifications without notice.



designed to be better™



Legrand, North America

3015 Kustom Drive
 Hebron, KY 41048
 United States
 844.334.8044
www.legrand.us/nuvo